

TECHNICAL SERVICE TRAINING

Welcome to another Scotsman technical service presentation, it will cover the MF Series Ice Flaker and Superflaker Machines models **MF 26, MF 36, MF 46, MF 56** and **MF 66.**

Flake Ice

Superflake Ice



Residual water content 25%



Residual water content 15%



NEW MF.6 SERIES



MF 26 A/W Model

Max daily Production = 120 Kg/24h*

* 10/10°C = Water and Air
Temperature

Flake Ice



Residual water content 25%



MF 36 A/W Model

Max Daily Production = 200 Kg/24h*

* 10/10°C = Water and Air
Temperature

Flake Ice



Residual water content 25%

Scotsman[®]
Ice Systems

NEW MF.6 SERIES



MF 46 A/W Model

Max Daily Production = 320 Kg/24h*

* 10/10°C = Water and Air
Temperature

Superflake



Residual water content 15%

Scotsman[®]
Ice Systems

NEW MF.6 SERIES



MF 56 A/W/RC Model

Max Daily production = 600 Kg/24h*

* 10/10°C = Water and Air
Temperature

Superflake Ice



Residual water content 15%

Scotsman[®]
Ice Systems

NEW MF.6 SERIES



MF 66 A/W/RC Model

Max daily production = 1150 Kg/24h*

* 10/10°C = Water and Air
Temperature

Superflake Ice



Residual water content 15%

TOPICS

On the next slides are shown the following steps by steps procedures:

- **UNPACKING**
- **INSTALLATION**
- **START UP AND OPERATIONAL CHECKS**
- **OPERATING PRINCIPLES and COMPONENTS**
- **MAINTENANCE**
- **SERVICE ANALYSIS**



NEW MF.6 SERIES

UNPACKING

UNPACKING

The machines are supplied in a carton box secured by two plastic strips to a wooden base. Check first the outside conditions of carton box and wooden base then cut the two plastic strips, remove the tape and then the carton box.




UNPACKING

Visually inspect
the exterior of
the machine
then unloose
the screws of
the front/top
panel.



UNPACKING

Remove the top panel then take out the water inlet and outlet hoses.



UNPACKING

Remove the two holding screws securing the ice machine to the wooden base....



UNPACKING

The Modular Flakers machines require for the installation the use of a companion storage bin to store the ice produced.

Storage bins required are:

- **SB 193 for MF 26 - 36**
- **SB 393 for MF 46 - 56**
- **SB 550 for MF 46 - 56**



UNPACKING

Unpack the storage bin and visually inspect the exterior then remove from the inside the carton box containing the legs as well as the drain hose and the plastic scoop.





NEW MF.6 SERIES

INSTALLATION

INSTALLATION

Install the four legs
and their
adjusting/leveling
nuts on the legs
socket as well as the
drain tube with its
clamp on the base of
the storage bin




INSTALLATION

Then install the machine on the storage bin with the proper adapter kit if necessary



INSTALLATION

Adequate space must be left for proper water and electrical connections on the rear side of the machine. A minimum clearance of 15 cm on both sides for best routing air.



INSTALLATION

Check the data plate of the machine located on the rear panel for correct voltage as well as for the proper wiring/fuse size.

Remember that all machines require a solid earth wire.




INSTALLATION


Check for the correct water and ambient conditions that should be:

- **Min. ambient temperature** **10°C (50F)**
- **Max. ambient temperature** **40°C (100F)**
- **Min. water temperature** **5°C (40F)**
- **Max. water temperature** **35°C (90F)**
- **Min. water pressure** **1 bar (14 PSI)**
- **Max. water pressure** **5 bar (70 PSI)**


INSTALLATION - AIR CIRCULATION



INSTALLATION - AIR CIRCULATION



INSTALLATION - AIR CIRCULATION



INSTALLATION

Level the unit on
both directions front
to rear and right to
left side using the
adjustable legs of the
storage bin.



INSTALLATION-ELECTRICAL

Install, on the cable supply with the machine, an adequate electrical plug according to the local standards and regulations.

Maximum voltage variation should be $\pm 10\%$.

Machine must be individually fuse protected.



INSTALLATION-WATER IN

Connect the 3/4" water inlet male thread to the water supply line by means of the rubber hose provided with machine.

Install on water supply line closed to the machine a water valve (tap).




INSTALLATION-WATER DRAIN

Connect the 20 mm O.D. fitting of the water drain with the flexible hose supply with the machine securing by its proper clamp.




AIR COOLED TYPICAL INSTALLATION




INSTALLATION-WATER IN

On the water cooled version there is a separate 3/4" male thread water inlet fitting connected directly to the water regulating valve that must be connect to the water supply line by means of the rubber hose provided with machine and.....




INSTALLATION-WATER DRAIN

.....a separate water drain fitting (3/4" gas male) that must be connected to the drain receptacle with a separate hose.



WATER COOLED TYPICAL INSTALLATION



**START UP
and
OPERATIONAL
CHECKS**


START UP AND OPERATIONAL CHECKS

Open the water tap/valve and Switch ON the power on the electrical supply line



COMPONENTS-ELECTRONIC CONTROLS


PC BOARD



START UP AND OPERATIONAL CHECKS


On PC Board the LED energized are:

• Power




START UP AND OPERATIONAL CHECKS

- Power
- 3' Waiting time (60' ONLY FOR MF 66 Model)



START UP AND OPERATIONAL CHECKS

The RED LED starts blinking for the first 3' (or for 60' on MF 66) while




START UP AND OPERATIONAL CHECKS


.....the water is entering
through the float valve
flowing then into the
vertical evaporator till it
reaches the same level



MF 26 and 36




MF 46-56-66



START UP AND OPERATIONAL CHECKS

After the first 3'
of waiting time
(60' for MF 66
model) the PC
Board supply
the power to
the drive motor
and....





NEW MF.6 SERIES

START UP AND OPERATIONAL CHECKS

.....few seconds

later starts up the

compressor



START UP AND OPERATIONAL CHECKS

On the air cooled version, as soon as the condensing temperature rises up to the CUT IN value of the condenser sensor, the fan motor starts to turn in **ON / OFF MODE**



START UP AND OPERATIONAL CHECKS

After two-three minutes the first pieces of flakes ice are discharged through the spout of the freezer dropping down into the storage bin



START UP AND OPERATIONAL CHECKS

The machine remains in operation producing continuously the flakes ice till the storage bin is completely full.

When same ice is accumulated into the ice chute




START UP AND OPERATIONAL CHECKS

.....it breaks the

Infrared beam


of the Optical

Ice Level control




START UP AND OPERATIONAL CHECKS

The breaking will
cause the
immediately the
SLOW blinking of
the **YELLOW LED**
.....



START UP AND OPERATIONAL CHECKS

.....and after
approximately 10
seconds the **PC**
Board switches OFF
the operation of the
compressor only
with the light **ON** of
bin full YELLOW
LED.





NEW MF.6 SERIES

START UP AND OPERATIONAL CHECKS

The PC Board keeps also the drive motor in operation for additional 3' after the tripping OFF at Bin Full, in order to clean up all ice from the inside of the evaporator.





NEW MF..6 SERIES

START UP AND OPERATIONAL CHECKS


This kind of Trip-OFF delay happens at :

- ◆ No water
- ◆ Too hi evaporating temperature
- ◆ Too hi condensing temperature

Only when the unit Trips OFF at Wrong/No/Slow rotation, the gear motor stops immediately.


START UP AND OPERATIONAL CHECKS

When ice is
removed from
the Optical Ice
Level Control
the Infrared
beam is
resumed
immediately.....




START UP AND OPERATIONAL CHECKS

And the **YELLOW**
LED of BIN FULL
will blink **FAST**
for 10 seconds
.....




START UP AND OPERATIONAL CHECKS

.....few seconds
later the YELLOW
LED is extinguished
and in the
meantime the RED
LED starts back
blinking for the 3
minutes waiting
time.



**OPERATING
PRINCIPLES
and
COMPONENTS**


OPERATING PRINCIPLES – REFRIGERANT



Scotsman[®]
Ice Systems

NEW MF.6 SERIES


OPERATING PRINCIPLES – WATER (MF 26-36 ONLY)




Scotsman[®]
Ice Systems

NEW MF.6 SERIES


OPERATING PRINCIPLES – WATER (MF 46-56-66 ONLY)




OPERATING PRINCIPLES – MECHANICAL




OPERATING PRINCIPLES – PC BOARD



OPERATING PRINCIPLES – PC BOARD



**OPERATING PRINCIPLES – PC BOARD
JUMPERS**





OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS

BIN FULL CONDITION:

Bin Full Yellow LED

ON STEADY





NEW MF.6 SERIES

COMPONENTS-ELECTRONIC CONTROLS

**OPTICAL ICE LEVEL
CONTROL**




OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS

NO WATER ALARM:

No Water Yellow LED

ON STEADY



Scotsman[®]
Ice Systems

NEW MF.6 SERIES

COMPONENTS-ELECTRONIC CONTROLS

**WATER LEVEL
SENSOR**




OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS

START UP DELAY TIME
3' or 60' (ONLY on MF 66)

Too Hi/Low Cond. Temp-
Stand-by RED LED

BLINKING




OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS

**TOO LOW AMBIENT
TEMPERATURE (<+3°C)**

Too Hi/Low Cond. Temp-
Stand-by RED LED

**BLINKS THREE TIMES
AND REPEAT**




Scotsman[®]
Ice Systems

NEW MF.6 SERIES

COMPONENTS-ELECTRONIC CONTROLS

**CONDENSER
SENSOR**



OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS



TOO HI CONDENSING

TEMPERATURE

(>60°C or >70°C)

Too Hi/Low Cond. Temp-
Stand-by RED LED

ON STEADY




Scotsman[®]
Ice Systems

NEW MF.6 SERIES

COMPONENTS-ELECTRONIC CONTROLS

**CONDENSER
SENSOR**





OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS

- NO
- SLOW (<1200 rpm)
- WRONG ROTATION
(Opposite direction)
OF DRIVE MOTOR

Wrong rotation/ Too Hi
Evap. Temp. YELLOW
LED



ON STEADY


OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS

**TOO HI EVAPORATOR
TEMPERATURE**

Wrong rotation/ Too Hi
Evap. Temp. YELLOW LED

**SLOW BLINKS AFTER 10'
OF OPERATION**





NEW MF.6 SERIES

COMPONENTS-ELECTRONIC CONTROLS

**EVAPORATOR
SENSOR**



OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS


**CONDENSER SENSOR OUT
OF ORDER**

No Water YELLOW LED

+

Stand-by Red LED

BOTH ON STEADY



OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS


**EVAPORATOR SENSOR OUT
OF ORDER**

No Water YELLOW LED

+

Stand-by Red LED

BOTH BLINKING



OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS


ICE LEVEL CONTROL OUT OF ORDER

No Water YELLOW LED

+

Stand-by Red LED

BLINKING ALTERNATE



OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS


**WATER CIRCUIT CLEANING
REMIND (6 or 12 months)**

No Water YELLOW LED →

+

Wrong Rotation YELLOW LED →

BOTH BLINKING




OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS

UNIT OFF DUE TO
JUMPERS IN ON TEST
CONTACTS

ALL LEDs

BLINKING




OPERATING PRINCIPLES – PC BOARD

ALARM CONDITION and LED MEANINGS

**ICE LEVEL CONTROL
CALIBRATION DONE**

ALL LEDs


BLINKING ONCE



COMPONENTS-ELECTRONIC CONTROLS


**INTERFACE PC
BOARD**

(MF 66 ONLY)




**OPERATING PRINCIPLES – INTERFACE PC BOARD
(MF 66 ONLY)**

The model MF 66 is equipped with a second PC Board connected to the Main One by means of two cable connectors



**OPERATING PRINCIPLES – INTERFACE PC BOARD
(MF 66 ONLY)**

The Interface PCB is equipped with one Push Button for IR Calibration and two Red LED (one for each Optical Ice Level Control)





NEW MF.6 SERIES

OPERATING PRINCIPLES – INTERFACE PC BOARD

It is **imperative** that both PC Boards used on model MF 66 must be of the **same manufacturer** (SYEN or Pro.El.Ind.).

If not the Main PC Board will keep the machine OFF all the time at Storage Bin Full - Yellow LED ON - without any ice into the storage bin.

Scotsman[®]
Ice Systems

**END FIRST
HALF**

